



KOMO®
product certificate
K52319/02



Issued 2017-08-15 Replaces K52319/01
Valid until Indefinite Dated 2009-10-01
Page 1 of 2

PB 5-layer pipe
NUEVA TERRAIN, S.L.

STATEMENT BY KIWA

This product certificate is issued on the basis of BRL 5605 Plastics piping systems of PB intended for heating installations: radiator connections dated 25 October 2016, conform the Kiwa-Regulations for Product certification.

The quality system and product characteristics in association with are assessed periodically.

On this basis Kiwa declares that a justified confidence exists, that the delivered by the certificate holder at delivery fulfil:

- the technical specification laid down in this product certificate,
 - the product requirements as laid down in this product certificate and in the BRL.
- provided that has/have been marked with the KOMO®-mark in a manner as indicated in this product certificate;

Luc Leroy
Kiwa

47317028

This product certificate is only valid in combination with a KOMO certified plastics piping system.

The certificate is listed in the overview on the website of Stichting KOMO: www.komo.nl.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.
Sir Winston Churchilllaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Holder of Certificate
NUEVA TERRAIN, S.L.
Apartado 444
Paduleta 2
01195 VITORIA
Spain
Tel. +34 (0)945290030
Fax +34 (0)945290024



Evaluated is:
quality system
product
Periodic inspection

PB 5-layer pipe

TECHNICAL SPECIFICATION**Subject**

PB 5-layer pipe

Product characteristics

The product complies to BRL 5605 Plastics piping systems of PB intended for heating installations: radiator connections

Specification

The dimensions of the pipe in the table below are part of this certificate.

Nominal outside diameter (mm)	Wall thickness (mm)
15	1,7
22	2,0
28	2,5

Colour: grey

MarkingsThe products shall be marked with the KOMO[®] mark.**Pipes**The minimum required marking on the pipes shall be:

- KOMO (or KOMO[®] word mark) + class 5/ 6 bar;
- certificate number of accompanying technical approval-with-product certificate of the piping system;
- the manufacturer's name, trade name, system name or logo;
- material identification: PB-H;
- the build up of the pipe: PB-H/EVOH/PB-H;
- nominal outside diameter and nominal wall thickness of the pipe in mm;
- production code.

The realization of the marks is as follows: clearly, durable and indelible at intervals of not more than 2 meters.

Logistics

Production and assembly of the system is laid down in the annex of the certification agreement.

APPLICATION AND USE

The products are intended to be used for piping systems for heating installations with an operating temperature profile according to class 5 of NEN-ISO 10508 and an allowable working pressure of maximum 6 bar.

RECOMMENDATION FOR THE CUSTOMER

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

if you should reject a delivery on the basis of the above, please contact:

- NUEVA TERRAIN, S.L.

and, if necessary:

- Kiwa Nederland B.V.

For the proper storage, transport and processing consult the instructions of the certificate holder.

